

Thermal Overload Relays

Tripping Class 20

New



ABB


Motor Protection — general

It is very important to choose an adequate protective device for the safety of the motor during operation and for its durability. The efficiency of protection methods varies according to the application. The overview below will help you to choose. There is no general rule and we are available to advise you for special applications and especially in the case of difficult starting. An economic and effective protection are thermal overload relays with protection against:

- > Overload
- > Phase failure imbalance
- > Phase loss

Description

- Available for starter construction with A Line contactors and separate panel mounting
- Designed for close couple mounting – separate base mounting available for all overload relays
- Full automatic function, Manual reset, Test phase or Reset can also be adjusted to function as a stop button
- Remote trip and reset option available
- Screwdriver guide holes, all terminal screws are available from the front
- Trip indication
- Ambient compensation -25 °C to +55 °C (-13 °F to +131 °F)



Tripping classes of the thermal overload relays

Standard tripping classes are 10 A, 10, 20, 30. The tripping class indicates according to IEC 60947-4-1 the maximum tripping time in seconds under specified conditions of test at 7.2 times the setting current and specifics tripping and non tripping times for 1.5 and 7.2 times the setting current.

Construction and function

• General

Thermal O/L relays and their accessories meet UL, NEMA, CSA and most other important international standards (IEC), European standards (EN) and the most important national standards. They meet the certification and approval directives required throughout the world.

Thermal overload relays are 3 pole. The motor current flows through their bimetals (1 per phase) which are indirectly heated. Under the effect of the heating, the bimetals bend, cause the relay to trip and the position of the auxiliary contacts to change. The relay setting range is graduated in amps. In compliance with international and national standards, the setting current is the motor nominal current and not the tripping current (no tripping at 1.05 x setting current, tripping at 1.2 x setting current). The tripping curves (cold or warm starting, 3 phases and 2 phases) are shown in the main catalog.

The relays are built to be self protecting in the event of an overload until the short circuit protection device is activated.

Function of the thermal overload relays

Press blue button	Contacts	Relay tripped		Relay not tripped	
		Manual	Automatic	Manual	Automatic
	NC 95-96 NO 97-98	open closed	open closed	closed open	closed open
Button R	NC 95-96	Reset	–	–	–
	NO 97-98	closes when Button's pressed	–	–	–
		opens when Button's pressed	–	–	–
Button R/O	NC 95-96	Reset	–	–	–
	NO 97-98	closes when Button's released	–	opens when Button's pressed closes when Button's released	opens when Button's pressed closes when Button's released
		opens when Button's pressed	–	–	–

Thermal Overload Relays with Trip Class 20

Ordering data for the "New additional Assortment"



TA25DU



TA42DU




TA75DU



TA80DU

Ordering Details Type	Order code	Setting range A ... A	UL Fuse/ 600V/K5 A	Packing unit piece	List Price
TA25DU trip class 20 for contactors A9 ... A40 and (T) AL9 ... (T) AL30					
TA25DU1.8-20	1SAZ211401R1025	1.3 ... 1.8	6	1	\$ 63
TA25DU2.4-20	1SAZ211401R1028	1.7 ... 2.4	10	1	
TA25DU3.1-20	1SAZ211401R1031	2.2 ... 3.1	10	1	
TA25DU4.0-20	1SAZ211401R1033	2.8 ... 4.0	15	1	
TA25DU5.0-20	1SAZ211401R1035	3.5 ... 5.0	20	1	
TA25DU6.5-20	1SAZ211401R1038	4.5 ... 6.5	25	1	
TA25DU8.5-20	1SAZ211401R1040	6.0 ... 8.5	35	1	
TA25DU11-20	1SAZ211401R1043	7.5 ... 11	45	1	
TA25DU14-20	1SAZ211401R1045	10 ... 14	60	1	
TA25DU19-20	1SAZ211401R1047	13 ... 19	60	1	
TA25DU25-20	1SAZ211401R1051	18 ... 25	70	1	
TA25DU32-20 ⁽¹⁾	1SAZ211401R1053	24 ... 32 ⁽¹⁾	100	1	
⁽¹⁾ with terminal block DX25: 1x16mm ²					
TA42DU trip class 20 for contactors A30, A40 and (T) AL30, (T) AL40					
TA42DU25-20	1SAZ311401R1001	18 ... 25	80	1	\$ 78
TA42DU32-20	1SAZ311401R1002	22 ... 32	100	1	
TA42DU42-20	1SAZ311401R1003	29 ... 42	150	1	
TA75DU trip class 20 for contactors A50 ... A75 and AE50 ... AE75					
TA75DU25-20	1SAZ321401R1001	18 ... 25	80	1	\$ 102
TA75DU32-20	1SAZ321401R1002	22 ... 32	100	1	
TA75DU42-20	1SAZ321401R1003	29 ... 42	150	1	
TA75DU52-20	1SAZ321401R1004	36 ... 52	175	1	
TA75DU63-20	1SAZ321401R1005	45 ... 63	200	1	
TA75DU80-20	1SAZ321401R1006	60 ... 80	250	1	
TA80DU trip class 20 for contactors A95, A110, AE 95 and AE110					
TA80DU42-20	1SAZ331401R1003	29 ... 42	150	1	\$ 135
TA80DU52-20	1SAZ331401R1004	36 ... 52	175	1	
TA80DU63-20	1SAZ331401R1005	45 ... 63	200	1	
TA80DU80-20	1SAZ331401R1006	60 ... 80	250	1	



Thermal Overload Relays with Trip Class 20

Resistances and power losses per phase

Short-circuit protection

Setting range	Short-circuit protection (fuses)		UL	UL	Resistance per phase	Power loss per phase
	Type „2“ co-ordination	Type „1“ co-ordination				
from ... to A A	gL/gG A	gL/gG A	Fuse/600V K5 A	600V CB A	mOhm	at upper current setting W
Thermal overload relay TA25DU trip class 20						
1.3 ... 1.8	10	25	6	-	670.3	2.2
1.7 ... 2.4	16	25	10	-	381	2.2
2.2 ... 3.1	16	25	10	-	235.3	2.3
2.8 ... 4.0	20	25	15	-	140.7	2.3
3.5 ... 5.0	25	25	20	-	91.2	2.3
4.5 ... 6.5	25	25	25	-	54.5	2.3
6.0 ... 8.5	32	32	35	-	32.1	2.3
7.5 ... 11	40	40	45	-	15.5	1.9
10 ... 14	50	50	60	-	12	2.4
13 ... 19	63	63	60	-	6.3	2.3
18 ... 25	80	80	70	-	4.7	3.0
24 ... 32	100	100	100	-	3.2	3.3
Thermal overload relay TA42DU trip class 20						
18 ... 25	100	160	80	80	5.5	3.43
22 ... 32	125	160	100	80	2.89	2.91
29 ... 42	160	160	150	80	1.84	3.24
Thermal overload relay TA75DU trip class 20						
18 ...25	100	160	80	80	5.5	3.43
22 ... 32	125	160	100	80	2.89	2.91
29 ...42	160	160	150	80	1.84	3.24
36 ... 52	200	200	175	125	1.3	3.51
45 ... 63	200	250	200	125	0.936	3.72
60 ... 80	250	250	250	125	0.615	3.94
Thermal overload relay TA80DU trip class 20						
29 ... 42	160	160	150	80	1.84	3.24
36 ... 52	200	200	175	125	1.3	3.51
45 ... 63	200	250	200	125	0.936	3.72
60 ... 80	250	250	250	150	0.615	3.94

Type „1“ co-ordination according to IEC 60947-4-1: Under short-circuit conditions, the starter shall cause no danger to persons or installation and may not be suitable for further service without repair and replacement of parts.

Type „2“ co-ordination according to IEC 60947-4-1: Under short-circuit conditions, the contactor or starter shall cause no danger to persons or installation and shall be suitable for further use. The risk of contact welding is recognized, in which case the manufacturer shall indicate the measures to be taken as regards the maintenance of the equipment

Standard technical data, operating data and dimensions see TA...Relay Main Catalog

Thermal Overload Relays with Trip Class 20

Technical data

Short-circuit ratings

Voltage 480 V	Type	Setting range A ... A	5 kA		10 kA		18 kA	
			Fuse K5	CB	Fuse K5	CB	Fuse K5	CB
TA25DU	TA25DU-1.8-20	1.3 ... 1.8	6	-	6	-	6	-
	TA25DU-2.4-20	1.7 ... 2.4	10	-	10	-	10	-
	TA25DU-3.1-20	2.2 ... 3.1	10	-	10	-	10	-
	TA25DU-4.0-20	2.8 ... 4.0	15	-	15	-	15	-
	TA25DU-5.0-20	3.5 ... 5.0	20	-	20	-	20	-
	TA25DU-6.5-20	4.5 ... 6.5	25	-	25	-	25	-
	TA25DU-8.5-20	6.0 ... 8.5	35	-	35	-	35	-
	TA25DU-11-20	7.5 ... 11	45	-	45	-	45	-
	TA25DU-14-20	10 ... 14	60	-	60	-	60	-
	TA25DU-19-20	13 ... 19	60	-	60	-	60	-
	TA25DU-25-20	18 ... 25	70	-	70	-	70	-
	TA25DU-32-20	24 ... 32	100	-	100	-	100	-
TA42DU	TA42DU-25-20	18 ... 25	80	80	80	-	150	-
	TA42DU-32-20	22 ... 32	100	80	100	-	150	-
	TA42DU-42-20	29 ... 42	150	80	150	-	200	-
TA75DU	TA75DU-25-20	18 ... 25	80	80	80	-	150	-
	TA75DU-32-20	22 ... 32	100	80	100	-	150	-
	TA75DU-42-20	29 ... 42	150	80	150	-	200	-
	TA75DU-52-20	36 ... 52	175	125	175	-	250	-
	TA75DU-63-20	45 ... 63	200	125	200	-	250	-
	TA75DU-80-20	60 ... 80	250	125	250	-	250	-
TA80DU	TA80DU-42-20	29 ... 42	150	80	150	-	150	-
	TA80DU-52-20	36 ... 52	175	125	175	-	175	-
	TA80DU-63-20	45 ... 63	200	125	200	-	250	-
	TA80DU-80-20	60 ... 80	250	150	250	-	250	-

Voltage 600 V	Type	Setting range A ... A	5 kA		10 kA		18 kA	
			Fuse K5	CB	Fuse K5	CB	Fuse K5	CB
TA25DU	TA25DU-1.8-20	1.3 ... 1.8	6	-	6	-	6	-
	TA25DU-2.4-20	1.7 ... 2.4	10	-	10	-	10	-
	TA25DU-3.1-20	2.2 ... 3.1	10	-	10	-	10	-
	TA25DU-4.0-20	2.8 ... 4.0	15	-	15	-	15	-
	TA25DU-5.0-20	3.5 ... 5.0	20	-	20	-	20	-
	TA25DU-6.5-20	4.5 ... 6.5	25	-	25	-	25	-
	TA25DU-8.5-20	6.0 ... 8.5	35	-	35	-	35	-
	TA25DU-11-20	7.5 ... 11	45	-	45	-	45	-
	TA25DU-14-20	10 ... 14	60	-	60	-	60	-
	TA25DU-19-20	13 ... 19	60	-	60	-	60	-
	TA25DU-25-20	18 ... 25	70	-	70	-	70	-
	TA25DU-32-20	24 ... 32	100	-	100	-	100	-
TA42DU	TA42DU-25-20	18 ... 25	80	80	80	-	150	-
	TA42DU-32-20	22 ... 32	100	80	100	-	150	-
	TA42DU-42-20	29 ... 42	150	80	150	-	200	-
TA75DU	TA75DU-25-20	18 ... 25	80	80	80	-	150	-
	TA75DU-32-20	22 ... 32	100	80	100	-	150	-
	TA75DU-42-20	29 ... 42	150	80	150	-	150	-
	TA75DU-52-20	36 ... 52	175	125	175	-	175	-
	TA75DU-63-20	45 ... 63	200	125	200	-	250	-
	TA75DU-80-20	60 ... 80	250	125	250	-	250	-
TA80DU	TA80DU-42-20	29 ... 42	150	80	150	-	150	-
	TA80DU-52-20	36 ... 52	175	125	175	-	175	-
	TA80DU-63-20	45 ... 63	200	125	200	-	250	-
	TA80DU-80-20	60 ... 80	250	150	250	-	250	-

Thermal Overload Relays with Trip Class 20

Table for tripping time

Tripping times of thermal overload relays as a function of a multiple of the setting current from cold state (tolerance +/- 20% of the tripping time).

Setting range	Tripping times of thermal overload relays: at multiple of setting current					
	3	4	5	6	7.2	8
from ... to A A	Tripping times in sec					

Thermal overload relays TA25DU trip class 20						
1.3 ... 1.8	47.1	27	20.3	15.8	12.7	11.5
1.7 ... 2.4	43.3	25	18.9	14.4	11.9	10.4
2.2 ... 3.1	47.5	28	20.8	16	13.1	11.8
2.8 ... 4.0	45.6	27	19.8	15.3	12.5	11
3.5 ... 5.0	47.8	29	21.2	16	13.2	11.8
4.5 ... 6.5	47.4	28	20.3	15.5	12.5	11
6.0 ... 8.5	46.1	27	20	15	11.7	10
7.5 ... 11	42.3	25	17.8	14.1	10.9	10.5
10 ... 14	39.4	25	16.8	13	9.9	8.5
13 ... 19	38.1	21	13.6	10	7.4	6.2
18 ... 25	44.4	25	16.1	11	9	8
24 ... 32	44.4	27	17.7	13	9.8	8.5
Thermal overload relays TA42DU, TA75DU, TA80DU trip class 20						
18 ... 25	51.6	29	20.3	15	11.7	10
22 ... 32	67.9	38	26.9	20	14.8	12.5
29 ... 42	58.8	33	22.5	16	12.2	10.3
36 ... 52	59.9	34	22.7	16	12.3	10.5
45 ... 63	65.8	34	22.4	16	12.4	10.5
60 ... 80	71.9	35	23.4	17	13.9	12



Publication LV043
No. 1SXU 106 043 B0201
Printed in USA, November, 2005

ABB Inc.
1206 Hatton Road
Wichita Falls, TX 76302
Telephone 888-385-1221; 940-397-7000
Fax 940-397-7085
<http://www.abb-control.com>

ABB Inc.
3299, J.B. Deschamps
Lachine, QC H8T 3E4
Canada
Telephone: 800-567-0283 (Quebec)
866-460-3300 (Ontario)
866-222-8368 (Calgary)
604-777-5477 (British Columbia)